



## **Description**

### **Features**

- Head of band saw moves left or right for angle cutting**
- Built-in protractor for fast and accurate selection of angles**
- One-step conversion from horizontal to vertical band saw**
- Stock remains in one position for all cuts**
- Portable-this band saw moves easily to the job site**

## Specifications

<b>Capacity (90° &amp; 45°)</b>	<b>10" Round at 90°</b> <b>8" Pipe at 90°</b> <b>11" Flat at 90°</b> <b>6-7/8" Round at 45°</b> <b>6" Pipe at 45°</b> <b>7-1/4" Flat at 45°</b> <b>10" H x 8" W at 90°</b> <b>8" H x 6" W at 45°</b>
<b>Blade Speeds (3)</b>	<b>55-115-230 FPM</b>
<b>Blade Size</b>	<b>10'0" x 1"</b>
<b>Feed Control</b>	<b>Hydraulic Adjusting</b>
<b>Vise</b>	<b>Quick Adjusting Camlock</b>
<b>Shut Off</b>	<b>Automatic</b>
<b>Motor - Standard</b>	<b>1 H.P. 110/220 Volt Single Phase</b>
<b>Optional</b>	<b>3 PH 220-440-460-480-575</b>
<b>Portable</b>	<b>10" Wheels-Standard</b>
<b>Shipping Weight</b>	<b>525 lbs.</b>
<b>Size</b>	<b>Table Height 27"</b> <b>Length 59"</b> <b>Width 24-3/4"</b> <b>Height 47"</b>
<b>Sealed Oil Bath Worm Gear</b>	<b>Standard</b>
<b>Removable Chip Tray</b>	<b>Standard</b>
<b>Construction</b>	<b>Heavy Steel; Welded &amp; Machined for Accuracy &amp; Durability</b>

## Accessories

<b>Air System</b>	<b>5922 (120V)</b> <b>5932 (230V)</b>
<b>2 Roller Support Stand With Stock Gauge and Micro Adjuster</b>	<b>6252</b>
<b>Single Stock Stand - 1 Roller</b>	<b>6185</b>
<b>Stock Stand - 5' Long (12"w) 4 - Rollers"</b>	<b>6229</b>
<b>Pipe Clamp Attachment for Camlock Vise</b>	<b>6106</b>
<b>Screw Type Vise</b>	<b>6620</b>
<b>Pipe Clamp Attachment for Screw Vise</b>	<b>6286</b>
<b>Vertical Table (10" x 16") with Blade Guard</b>	<b>9374</b>